



| | |
|----|-----|
| 1 | VDD |
| 2 | VDD |
| 3 | VSS |
| 4 | VSS |
| 5 | VSS |
| 6 | RD |
| 7 | WR |
| 8 | RS |
| 9 | CS0 |
| 10 | RST |
| 11 | D0 |
| 12 | D1 |
| 13 | D2 |
| 14 | D3 |
| 15 | D4 |
| 16 | D5 |
| 17 | D6 |
| 18 | D7 |
| 19 | K |
| 20 | A |

- 1 DISPLAY TYPE : CSTN
- 2 VIEWING DIRECTION: 6:00
- 3 POLARIZER MODE: TRANSMISSIVE/NEGATIVE
- 4 DRIVE METHOD :1/64 DUTY 1/9 BIAS
- 5 LCD OPERATION VOLTAGE: 8.7V
- 6 RECOMMEND VDD=3.0V
- 7 OPERATION TEMP : -20°C--70°C
- 8 STORAGE TEMP: -30°C--80°C
- 9 IC : UC1682XGA
- 10 BACKLIGHT: LED(WHITE)
- 11 UNMARKED TOLERANCE: ±0.3mm

DETAIL A:
Scale:20x



DETAIL B:



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

| | | |
|---------------|---------------------------|----------|
| DRAWN BY: | TITLE: TM9664FKFWG1 | |
| CHECKED BY: | DWG NO: G-1 | |
| APPROVED BY: | DWG NAME: TM9664FKFWG1 G- | SCALE: |
| CONFIRMED BY: | SHEET NO: 1 OF 1 | UNIT: mm |