

Feature

1. Color R,G,B LCD type
2. 320RGB 240 dots
3. 8-bit data bus
4. Built-in White backlight(CCFL)
5. +3~+5V power supply
6. 1/240 duty cycle

Pin NO.	Symbol	Function
1	FRM	Scan start-up signal
2	LOAD	Data latch
3	CP	Data shift
4	DISP	Display enabl signal
5	VDD	Power supply fo logic
6	VSS	Ground
7	VEE	Power supply for LCD
8	DB7	Display data bus
9	DB6	Display data bus
10	DB5	Display data bus
11	DB4	Display data bus
12	DB3	Display data bus
13	DB2	Display data bus
14	DB1	Display data bus

IT	Symbol	Display Data Bus
15	DB0	Display data bus

Mechanical Data

Item	Standard Value	Unit
Module Dimension	154.6×114.8×8.5	mm
Viewing Area	118.18×89.38	mm
Dot Size	0.09×0.33	mm
Dot Pitch	0.12×0.36	mm

Absolute Maximum Rating

Item	Symbol	Standard Value			Unit
		min.	typ.	max.	
Power Supply	VDD-VSS	2.7	3.0	3.3	V
		4.7	5.0	5.3	
Input Voltage	VI	0.8V _{DD}	---	VDD	V

Note : VSS=0 Volt, VDD=5.0 Volt.

Electronical Characteristics

Item	Symbol	Condition	Standard Value			Unit
			min.	typ.	max.	
Input Voltage	VDD	L level	0.8V _{DD}	---	V _{DD}	V
	VIO	H level	V _{SS}	---	0.2V _{DD}	V
Supply Current	IDD	VDD=5V	---	---	---	mA
Recommended LC Driving		0°C	---	---	---	

Recommended LC Driving Voltage for Normal Temp. Version module	VEE-VSS	0°C	---	---	---	V
		25°C	---	26.2	---	
		50°C	---	---	---	
Power consumption	---	VDD=5V VEE=26.2V	---	2.0	---	mA